

АСФАЛЬТОБЕТОННЫЙ ЗАВОД XCMG XAP320



Асфальтобетонный завод XCMG XAP320 является профессиональным оборудованием для производства асфальтобетонной смеси в объемах до 320 тонн в час. Завод оснащен современным оборудованием для подготовки и смешивания компонентов, а также имеет системы автоматического контроля качества. Занимаемая площадь завода составляет 1677 квадратных метров, и его можно установить как на постоянной, так и на временной основе на строительных площадках.

ТЕХНИЧЕСКИЕ ХАРАКТЕРИСТИКИ

Nominal Output (allowable aggregate moisture 5%) (t/h)	320
Oil Heater Temperature Deviation Coefficient (°C)	±5
Total Installed Power (kW)	782
Length x Width x Height (m)	43 x 39 x 22
Occupied Area (m ²)	1677
Quantity x Volume (m ³)	6 x 16
Drying Cylinders	2.8
Diameter (m)	10.8
Fuel	Diesel, Heavy Oil / Natural Gas
Dust Removal Method	Gravity Dust Removal + Secondary Bag
Bag Filter Area (m ²)	1404
Number of Screen Layers	6
Screening Area (m ²)	66.3
Total Weighing Hopper Weight (kg)	5000
Powder Weighing Hopper Weight (kg)	500
Bitumen Weighing Barrel Weight (kg)	500
Mixing Power (kW)	2 x 55
Mixing Capacity (kg/batch)	4250
Bitumen Tank (litres)	4 x 50000